Inspection checklist for appliances used in sugarcane production

App	Applicant details			
Nam	Name			
Add	Address			
Tow	Town Postcode			
Pho	Phone Number E-mail	I		
App	Appliance Information			
Тур	Туре			
Mal	Make Model			
Ser	Serial number			
_	Sugarcane harvesters Each area must be inspected carefully for soil and residues in rec	esses		
1.	Topper arms, drum and blades - note directional flaps			
2.				
3.	3. Crop dividers - inspect top recess			
4.	4. Knockdown and finned rollers			
5.	5. Basecutter			
6.	. Feed roller train - remove all compacted contaminants			
7.	. Chopper system - clean area above deflector plate			
8.	. Primary extractor blades and chamber - inspect corners for compacted soil			
9.	Elevator system - inspect channels, sprockets, flights			
10.	0. Elevator boot- remove logged billets			
11.	Secondary extractor blades and chamber			
12.	12. Motor screen and covers			
13.	13. Hydraulics and lines			
14.	14. Operators cabin			
15.	15. Wheels and tracks			
16	16 All oxtornal and internal curfaces			

Tractors 1. Operators cabin 2. Radiator 3. Engine and covers 4. Wheels - particularly inside of rims 5. All external and internal surfaces

Planters		
1.	Furrow openers	
2.	Chopper knives (whole stalk)	
3.	Chute	
4.	Hoppers	
5.	Elevator flights, boot, dip tank on billet planters	
6.	Rotate elevators (if applicable) - remove lodged billets	
7.	All external and internal surfaces	

Haul-outs, cane-trailers and bins		
1.	Tractor or prime mover - as above	
2.	Wheels - particularly inside of rims	
3.	Suspension under bin	
4.	Flights, boot, hopper on elevator bins Rotate elevators (if applicable) - remove lodged billets	
5.	Inside and outside of bin	

6. All external and internal surfaces